

# BIGUMA<sup>®</sup>-Additiv W

Additive to optimise the performance properties of sheet pile casting

## Use

BIGUMA<sup>®</sup>- Additiv W is an additive to optimise the performance properties of sheet pile casting when working with filled sheet pile interlocks at low ambient temperatures. BIGUMA<sup>®</sup>- Additiv W improves the plasticity and flexibility of the casting compound, so that even at outside temperatures below 0 °C a problem-free installation of the grouted sheet piles is possible.

## Properties

BIGUMA<sup>®</sup>- Additiv W is a special liquid additive for improving the plasticity and flexibility of sheet pile casting at low outside temperatures.

BIGUMA<sup>®</sup>- Additiv W is characterised by the following features and properties:

- Liquid at room temperature
- Special additive for increasing the plasticity and flexibility
- Not a hazardous substance as defined in regulations

## Application instructions

BIGUMA<sup>®</sup>- Additiv W is a viscous liquid at room temperature, which is added directly into the cooker during the melting process of the casting compound. The amount added is approx. 2 to 3 % by weight on the quantity of the casting compound. After supplementing the additive, the material in the stove should be stirred to ensure homogeneous distribution. BIGUMA<sup>®</sup>- Additiv W should be used during driving at ambient temperatures below 0 °C. It is not necessary at higher ambient temperatures.

## Material consumption

The proportion of BIGUMA<sup>®</sup>- Additiv W is approx. 2 to 3 % by weight related to the quantity of the casting compound.

## Storage

The product has a useful life of at least 24 months when stored in a cool and dry place.

## Form of supply

Canister: 25 l

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at [www.dga.de](http://www.dga.de).

Rev.: 01/23

## Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37    @ info@dga.de    🌐 [www.dga.de](http://www.dga.de)