

BIGUMA®-CS Tape

Polymer bitumen based sealing tape

Use

BIGUMA®- CS Tape is used for sealing open seams and cracks up to a width of 3 mm in asphalt pavements. The tape covers the seam or crack area and effectively prevents the penetration of surface water. Preferably BIGUMA®- CS Tape is used for minor roads in local road construction, as well as for pavements and cycle paths.

Properties

BIGUMA®- CS Tape distinguishes itself by the following characteristics:

- cold application, therefore problem-free handling
- smaller damage can be repaired quickly
- can be covered with asphalt mixture
- high ageing resistance by the usage of polymer modified bitumen
- resistant against aqueous solutions, salts and thinned acids, or similar
- bituminous building material and therefore problem-free recyclable

Application instructions

The seam/crack area must be dry and free from loose debris. The primer COLZUMIX®- VfB is brushed on both sides of the area. The quantity of the primer depends on the subsoil. In any case an overdose must be avoided. After the primer had dried of BIGUMA®- CS Tape is rolled out and put under light pressure on the crack area. The silicone paper is removed, afterwards the surface can be covered with crushed stone fines for blunting and BIGUMA®- CS Tape is then pressed down using a roller.

Note: If the temperature is lower than 10 °C the adhesion properties can be improved by warming the asphalt with a propane flame.

Form of supply

Thickness:	approx. 3 mm
Roll length:	22 m
Roll width:	40 mm (standard)

Packing units

2 rolls/carton (44 m)

Storage

The product has to be stored cold and dry and is storable for at least 12 months.

Cleaning agent

Equipment:	BIGUMA®- SWS, petrol and commercial solvents
At skin contact:	hand washing paste

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/25

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de