



Cold cleaner for cleaning and removing bitumen

Use

BIGUMA®- SWS is a cold cleaner serving to clean and remove bitumen.

Properties

BIGUMA®- SWS is distinguished by the following characteristics:

- cold cleaner with an emulsifying effect
- excellent at dissolving bitumen, grease and oil
- washes well with water

Application instructions

BIGUMA®- SWS is sprayed undiluted onto the object to be cleaned. After allowing the cleaner to act for a short while, the dissolved dirt is wiped off, e.g. with a cloth. Once the product has been applied, a brush made of natural hair can also be used to assist with cleaning. The object to be cleaned is then washed off with water. The above dirt can be removed easily thanks to the combined dissolving and emulsifying effect by BIGUMA®- SWS. Because of the solvent components, the resistance of the objects to be treated must be checked in advance, especially on painted or plastic surfaces.

Storage

The product can be stored for at least 36 months in the unopened container. The containers must be kept away from frost. Avoid direct sunlight or strong heat.

Form of supply

Spray nozzle:	600 ml
Plastic container:	5 l, 10 l
IBC:	1,000 l

Safety information

Keep away from heat, hot surfaces, sparks, naked flames as well as other ignition sources. No smoking. Do not spray towards naked flames or other ignition sources. Do not pierce or burn, not even after use. Avoid inhaling dust / smoke / gas / mist / vapour / aerosol. Wear protective gloves / protective clothing / eye protection / face protection. IN CASE OF CONTACT WITH EYES: Rinse carefully with water for several minutes. Remove contact lens if possible. Continue rinsing. Contact POISON INFORMATION CENTRE / doctor immediately. Do not expose to sunlight and temperature above 50°C / 122°F. Dispose of content / container in accordance with official regulations. Do not dispose of can in domestic waste after use, but instead send fully emptied for recycling collection.

Hazard warnings

Extremely flammable aerosol. Container is pressurised: Can burst upon heating. Causes skin irritation. May cause allergic skin reactions. Causes serious damage to the eyes. Toxic to water organisms, with long-term effect.

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de

Hazardous components

Orange terpenes, dodecylbenzenesulphonic acid, compound with 1-Aminopropan-2-ol (1:1) alcohols, C12-14, ethoxylated, docusate sodium (sodium 1,4 to [(2-ethylhexyl)oxy]-1,4-dioxobutan-2-sulphonate).

Other hazards



The formation of explosive/highly flammable mixtures is possible in case of inadequate ventilation and/or through use.

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/24

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

 Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany +49 231 395797 - 37  info@dga.de  www.dga.de