COLZUMIX®-VFB





Solvent containing precoat for bitumen based joint tapes

Use

COLZUMIX®- VFB is a bituminous pre-coating material for the meltable bitumen based joint tape BIGUMA®- Band.

Properties

COLZUMIX®- VFB fulfils the requirements of AIB.

The primer is

- set ready to use
- fast setting, penetrating into pores and dust binding

Application instructions

The joint flank must be dry, clean free from frost as well as from oil and greases. Loose particles have to be removed. COLZUMIX®- VFB can be applied by brush or by spraying. The drying time depends on the weather conditions. The application of the joint tape can take place if the primer is dry; that means when it is touch dry. At working stops the opened tin has always to be closed again.

Theoretical material consumption

approx. 0.02 litres per running meter

Hazard note

R 10: inflammable

Storage

In unopened original tins COZUMIX®- VFB can be stored for at least 12 months. Flammable liquids ordinance (VbF): A II

Supply form

5 I and 10 I tins

Cleaning agents

Equipment: BIGUMA®- SWS, petrol and commercial solvents

In case of skin contact: Hand cleansing paste

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

Producer







Technical data

Kind of binder: bitumen Kind of solvent: white spirit Nature: fluid

Flash point (DIN 53 213): > 21 °C

Density (DIN 52 004): approx. 0.84 g/cm³

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/21

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

Producer

Plant Isoliererzeugnisse Großröhrsdorf

Mafenbahnhof 10 ■ 44147 Dortmund ■ Germany