

DOBAU®

- 2SA Dichtungsband



DOBAU®- 2SA Sealing Tape

Two-sided adhesive bitumen sealing strip

Product description

DOBAU®- 2SA Dichtungsband (DOBAU®- 2SA Sealing Tape) is a double-sided adhesive sealing and installation strip made of polymer-modified bitumen without an HDPE carrier film. It is used as a complement to DOBAU®- Abdichtungsbahn KSK (DOBAU®- Sealing Membrane) (cold-applied, self-adhesive masonry waterproofing according to DIN EN 13969 and DIN SPEC 20000-202: 2016-03; Tables 18 and 19).

Use

For improved bonding of longitudinal and transverse joints under the DOBAU®- Abdichtungsbahn KSK (additional adhesive strength), at wall-floor transitions, inside and outside corners, edges, sealing joint sheets, and details such as pipe connections, floor drains, etc. It can also be used for securing insulation and drainage boards and as a coating on expansion joint sheets.

DOBAU®- 2SA Dichtungsband is suitable for both vertical and horizontal applications on walls, floor slabs, foundations, basement walls, concrete foundations, underground garages, and other suitable substrates made of flat concrete, screed, OSB, etc.

Properties

DOBAU®- 2SA sealing tape is a double-sided adhesive bitumen sealing strip.

It is characterised by the following features:

- easy to process and apply by peeling off the first release liner and, in a second step, removing the siliconized backing paper
- self-adhesive on both sides, good crack bridging and leveling of small unevenness
- ideal for attaching insulation boards to the DOBAU®- Abdichtungsbahn KSK and expansion joint sheets
- perfect as reinforcement for, e.g., corners, surface transitions, pipe, duct, and cable penetrations in basement waterproofing
- can be used without primer from +5 °C to +40 °C

Technical data

Thickness:	1.0 mm other versions in the range of 0.5 to 2.5 mm are available on request
Standard With:	300 mm; other dimensions on request
Standard Length:	10 m; other dimensions on request
Optimal Processing Temperature:	+5 °C to +40 °C

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/25

Technical data sheet page 1

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de