

DOBAU® -Bitumenkleber LO



DOBAU®- Bitumen Adhesive LO

Fibrous, cold-applied bitumen adhesive and filler

Use

DOBAU®- Bitumenkleber LO (DOBAU®- Bitumen Adhesive LO) is used to repair and seal imperfections on roofing made of bitumen roofing membranes, as well as on openings, ends and connections, etc. The filler adheres well to mineral substrates (concrete, brickwork, plaster). When used on steel or other non-absorbent substrates, a maximum thickness of 4 cm may be applied. The material properties only develop fully after complete drying.

Properties

DOBAU®- Bitumenkleber LO is a fibre-reinforced, bitumen putty sealing compound on a bitumen-solvent basis and is characterised by the following features:

- Cold workable
- Supplied ready for use
- Adheres well to concrete, brickwork, plaster, bitumen membranes and steel
- Not frost sensitive
- Protects against moisture

Application instructions

Suitable substrates are concrete, brickwork, plasters or timber. The substrate must be smooth, firm, dust-free and free from dirt and nests. For better adhesion, it is recommended to prime the substrate using DOBAU®- Voranstrich L. Corroded surfaces should be cleaned of rust. Spread the product onto the substrate and let it run out at the edges. Try not to exceed a single layer thickness of 5 mm. Apply thicker layers in several sweeps and always only after the solvent has evaporated, otherwise blistering and a very long drying time cannot be ruled out. Do not apply the product to hot or easily heated substrates.

In cold weather, the filler must first be stored in a heated room. To improve adhesion before applying DOBAU®-Bitumenkleber LO, the substrate should be treated with DOBAU®- Voranstrich L. The application temperature should be between 5 °C and 35 °C. DOBAU®- Bitumenkleber LO can be applied using a spatula or similar tool. The product contains solvent, which can attack synthetic materials, etc. Compatibility with the substrates must be examined.

Technical data

Colour:	black
Basis:	bitumen; solvent
Consistency:	viscous, spreadable
Film-forming constituents:	approx. 80 %
Density:	1.3 g/cm ³
Compliant with Operational Safety Regulations:	flammable
Use:	approx. 1.2 kg/m ² per mm layer thickness

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de

Storage

Can be stored unopened upright in the original container for at least 18 months. Protect from direct sunlight, keep cool and dry.

Form of supply

5 kg Bucket	75 Package/Pallet
10 kg Bucket	45 Package/Pallet
25 kg Bucket	18 Package/Pallet

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/24

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de