

# DOBAU® -Nageldichtband ESK



## DOBAU®- Nail Sealing Tape SSA (formerly ISO- Nail sealing tape N)

One-sided, cold self-adhesive, carrier-free elastomeric tape based on polymer bitumen

### Use

The DOBAU®- Nageldichtband ESK is a one-sided, cold self-adhesive, carrier-free elastomeric tape based on polymer bitumen for sealing nail joints in the roof area.

### Structure

The polymer bitumen is laminated onto the one-side siliconised PP film. The film also serves as a separating film.

### Technical data

Thickness:	2.0 mm ± 0.2 mm
PP-Folie:	0.04 mm
Colour:	black

### Application fields

For sealing nail penetrations in roofing membranes.

### Application

The DOBAU®- Nageldichtband ESK is laid on the laid underlay in the rafter area. The counter lath is then applied and nailed on. The nail penetrations in the film are sealed again afterwards by the elastic behaviour of the nail sealing tape.

### Application temperature

From approx. 5 °C

When used in cold weather, the DOBAU®- Nageldichtband ESK should be stored for at least 12 hours in an environment with > 10 °C.

### Form of supply

Roll width:	50 mm, 60 mm, 70 mm, 80 mm
Roll length:	10 m

### Storage

The product should be protected from direct sunlight and stored at 10 °C to 30 °C.

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at [www.dga.de](http://www.dga.de).

Rev.: 01/23

Technical data sheet page 1

#### Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37    @ info@dga.de    🌐 www.dga.de