

DOBAU®

-Petrolatum uni



Petrolatum-coated chemical fibre reinforcement

Structure

DOBAU®- Petrolatum uni is a corrosion protection tape, consisting of a chemical fibre reinforcement (80 g/m²), coated on both sides with a modified petrolatum compound of high adhesive force and elasticity.

Technical data

Weight:	approx. 1.4 kg/m ²
Thickness:	1.0 mm ± 0.1 mm
Stability:	UV resistant
Colour:	beige to brown (Colour deviations do not have any effect on quality)

Application field

For subsequent coating of weld seams areas and shaped parts as well as fittings, house connections, flanges and in lightning protection construction. Ideally suitable for difficult areas in conjunction with DOBAU®-mastic.

Operating temperature up to 30 °C

Processing

The area to be coated must be made free of rust and cleaned thoroughly using a wire brush. The surface must be dry and free of grease. The tape must be applied in 3 layers to attain a high corrosion protection effect. We therefore recommend applying the first winding with a minimum of 50 % overlap. The top layer should be applied in a spiral shape with 10 mm overlap. It begins and ends 50 mm on the adjoining factory coating. Ensure crease-free winding without cavity formation. Finally, the tape must be pressed down again and smoothed, especially in the overlap area. In case of increased mechanical load, we recommend attaching the ISO pipe protection mat additionally.

Form of supply

Roll length:	10 m				
Width in mm:	50	100	150	200	
Packing unit/box:	24	12	12	6	rolls

Storage

protected against direct sunlight, dry,
standing on the cut edges,
stacking height max. 4 boxes

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/23

Technical data sheet page 1

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de