



Black roof coating

Use

DOBAU®- Schutz- und Dachanstrich is a roof coating for roofing membranes and other bituminous roof coverings. It also has a sealing effect against ground moisture on floor slabs and on walls of components in contact with the ground.

Properties

DOBAU®- Schutz- und Dachanstrich is distinguished by the following characteristics:

- Roof coating for roofing membranes
- can also be used effectively on slightly damp substrate
- good adhesion on bituminous and mineral substrates

Application instructions

Substrate

Building areas must be firm, smooth, free of nests, gaping cracks and burrs as well as free of impurities. Unclosed recesses that are larger than 5 mm, such as mortar pockets, open butt and horizontal joints or outbreaks, must be closed with suitable mortar. Open butt joints to 5 mm and surface profiles or uneven areas of stones must be closed or equalised either by plastering (thin or levelling plaster) or sealing muds.

Weather conditions

At the application of DOBAU®- Schutz- und Dachanstrich the ground and air temperatures have to be more than 5 °C. The effects of water, rain and frost must be avoided during the processing and drying phase.

Establishing the seal

The protective coat is applied in minimum two layers, e.g. with a paintbrush, spatula, fine brush or similar. The following coatings may only be applied after the previous layer has fully dried. The coating is dried once it adheres firmly to the substrate. To make it easier to clean the tools later, these must be moistened before use and cleaned with water immediately afterwards.

Material consumption

One coat requires approx. 0.4 - 0.5 kg/m²

Storage

Can be stored for at least 12 months in the unopened container. Opened containers can be stored by placing the film back over the remaining amount and keeping the container well closed. The containers must be kept away from frost. Avoid direct sunlight or strong heat.

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de

DOBAU®-Schutz- und Dachanstrich

Form of supply

Plastic bucket: 5 kg, 10 kg, 25 kg

Cleaning agent

At skin contact: Hand cleansing paste

Tools and other objects can be cleaned with water when fresh and when set with BIGUMA®- SWS.

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/23

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de