



## DOBAU®- SOS Tape

One-sided, cold self-adhesive, highly stretchable, diffusion-tight bitumen tape based on elastomeric bitumen for universal sealing involving penetrations of any kind in outdoor areas, e.g. chimneys, roof windows etc. Also suitable for sealing indoors, e.g. thresholds.

### Structure

DOBAU®- SOS Band consists of an external HDPE special film coated with high-quality elastomeric bitumen. A siliconised film is used as separating material. This ensures optimum storage stability and application.

### Technical data

Thicknesses (DIN EN 1849-1):	1.5 mm ± 0.2 mm or 1.2 mm ± 0.15 mm
Mass per unit area DIN EN 1849-1:	1.5 kg/m <sup>2</sup> ± 0.2 kg/m <sup>2</sup> or 1.2 kg/m <sup>2</sup> ± 0.15 kg/m <sup>2</sup>
Cold bending behaviour (DIN EN 1109):	-20 °C
Adhesive strength (DIN EN 1939):	≥ 60 N/25 mm
Softening point (DIN EN 1427):	≥ 85 °C

### Application fields

- Protection against water, steam and driving rain in buildings (e.g. window connections)
- Condensation water protection for ventilated facades
- Threshold sealing in interior areas

### Application

The sealing surface must be resistant to abrasion, grease and dust. Sharp-edged unevenness must be removed. After removing the separating foil, the bitumen tape can be applied to the sealing surface. DOBAU®- SOS Band must be firmly pressed on after application. The formation of hollow areas (bubbles) must be avoided. To improve adhesion, the sealing surfaces can be painted with the primer COLZUMIX®-Haftgrund. After the primer has flashed off, the DOBAU®- SOS Band can be laid. Substrates that can be walked on or driven on are not suitable for application.

### Form of supply

Roll width: 75 mm/ 100 mm/ 200 mm  
Roll length: 10 m  
Other PU available on request.

## Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37    @ info@dga.de    🌐 www.dga.de

## Storage

The product should be protected from direct sunlight and stored at 5 °C to 40 °C.  
The rolls should also be stored dry and standing on their cut edges. The product is not vulnerable to frost.  
The properties of DOBAU®- SOS Band remain unchanged for a long time. We recommend application within 12 months.

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at [www.dga.de](http://www.dga.de).

Rev.: 01/23

### Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37    @ info@dga.de    🌐 [www.dga.de](http://www.dga.de)