

DOBAU® -Spachtelmasse Duo



Fibre-reinforced filler

DUO-Technology

The properties of environmentally friendly bituminous emulsion and those of solvent-based bitumen coatings have been combined in DOBAU®- Duotechnology. This means the protective coating can be diluted with water. It is also not flammable and low in VOC. Besides this, the special combination of bonding agents allows for a very high penetration capacity into standard building substrates and ensures an optimal bond with the bituminous product to be applied.

Use

DOBAU®- Spachtelmasse Duo serves for repairing cracks, joints, valleys etc. as well as for sealing chimney connections and wall ties, openings etc.

Properties

DOBAU®- Spachtelmasse Duo is distinguished by the following characteristics:

- for repairing roofing membranes
- for repairing roof valleys
- supplied ready for use
- does not turn brittle in cold temperatures
- does not run off in hot temperatures

Application instructions

Substrate

The substrate to be coated must be dry and free of oils, greases and loose components.

Weather conditions

At the application of DOBAU®- Spachtelmasse Duo the ground and air temperatures have to be more than 5 °C. Water and frost effect have to be avoided during the total time of application and drying.

Execution of the sealing

The filler is typically applied with a trowel, spatula or smoother. The total layer thickness can be up to 4 mm per work step. The second layer may only be applied after the first layer has fully cured.

The drying time at 23 °C and 50 % rel. humidity is approx. 1 mm/24 hours.

Theoretical material consumption

for 1 mm dry layer thickness approx. 1.4 kg/m²

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de

Producer

Plant Wm. Hilgers

Storage

Can be stored for at least 12 months in the unopened container. Opened containers can be stored by placing the film back over the remaining amount and keeping the container well closed. The containers need to be stored frost free. Avoid direct sunlight or strong heat.

Form of supply

Plastic bucket: 1 kg, 5 kg, 10 kg

Cleaning agent

At skin contact: hand washing paste

Tools and other objects can be cleaned with water when fresh and when set with BIGUMA®- SWS.

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/22

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de

Producer

Plant Wm. Hilgers