

DOBAU® -Voranstrich Duo



DOBAU®- PRIMER DUO

Low solvent bitumen primer

DUO Technology

The properties of environmentally friendly bituminous emulsion and those of solvent-based bitumen coatings have been combined in DOBAU®- Duo technology. This means the protective coating can be diluted with water. It is also not flammable and low in VOC. Besides this, the special combination of bonding agents allows for a very high penetration capacity into standard building substrates and ensures an optimal bond with the bituminous product to be applied.

Use

DOBAU®- Voranstrich Duo serves as a primer for hot or cold applied bituminous paint, coatings and spray compounds, as well as for bituminous roofing membranes and self-adhesive, cold applied sheets.

Properties

DOBAU®- Voranstrich Duo is distinguished by the following characteristics:

- reaches dust dryness quickly thanks to special Duo Technology
- high penetration capacity into standard building substrates
- excellent dust binding properties
- can also be used effectively on slightly damp substrate
- low VOC content, thus environmentally friendly
- good adhesion on bituminous and mineral substrates
- resistant to water and diluted acids, salts, lime and cement when set
- high adhesive strength

Application instructions

Weather conditions

DOBAU®- Voranstrich Duo is sensitive to frost. Completely dry coatings are not sensitive to frost. At the application of DOBAU®- Voranstrich Duo the ground and air temperatures must be more than 5 °C. The effects of water, rain and frost must be avoided during the processing and drying phase.

Substrate and implementation

The substrate to be coated must be free of oils, grease and loose components. Before processing, the primer must be fully homogenized by stirring. It can be applied by either painting or spraying. To make it easier to clean the tools later, these must be moistened before use and cleaned with water immediately afterwards.

Theoretical material consumption

approx. 0.2-0.3 kg/m², depending on the substrate

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de

Storage

It can be stored for at least 12 months in an unopened container. Opened containers can be stored by keeping the container well closed. The containers need to be stored frost free. Avoid direct sunlight or strong heat.

Form of supply

5 liter bucket:	60 buckets per pallet
10 liter bucket:	44 buckets per pallet
25 liter bucket:	18 buckets per pallet
5 liter can:	60 cans per pallet
10 liter can:	60 cans per pallet
20 liter can:	24 cans per pallet

Suitable system products

DOBAU®- Plast S

Cleaning agent

When fresh:	Water
When set:	DOBAU®- SWS Bit-Cleanser, common solvents or benzine
At skin contact:	Hand washing paste

Note

Contains: rosin; colophony; 1,2-benzisothiazol-3(2H)-one; 1,2-benzisothiazolin-3-one; 2-Methyl-2H-isothiazol-3-on (MIT) May cause allergic reactions. Safety data sheet available on request.

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/23

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de