

DOBAU® -Voranstrich E



DOBAU®- PRIMER E

Water-based bitumen primer

Use

DOBAU®- Voranstrich E is a primer and adhesive base with high penetration capacity into mineral substrates such as concrete, brickwork and rendering. DOBAU®- Voranstrich E serves as a primer for DOBAU®- 1KS and DOBAU®- 2KS as well as hot or cold applied bituminous paint and coating compounds, plus bituminous roofing membranes.

Properties

DOBAU®- Voranstrich E is distinguished by the following characteristics:

- supplied ready for use
- can also be used effectively on damp substrate
- solvent-free and environmentally friendly
- good adhesion on bituminous and mineral substrates
- suitable for interior use
- resistant to water and diluted acids, salts, lime and cement
- sets quickly, closes pores and binds dust, especially when applied with a brush

Application instructions

Substrate and implementation

The substrate to be coated must be free of oils, grease and loose components. Before processing, the primer must be fully homogenized by stirring. It can be applied by either painting or spraying. To make it easier to clean the tools later, these must be moistened before use and cleaned with water immediately afterwards.

Weather conditions

DOBAU®- Voranstrich E is sensitive to frost. Completely dry coatings are not sensitive to frost. At the application of DOBAU®- Voranstrich E the ground and air temperatures must be more than 5 °C. The effects of water, rain and frost must be avoided during the processing and drying phase.

Theoretical material consumption

approx. 0.2 - 0.3 kg/m², depending on the substrate

Storage

Can be stored for at least 12 months in an unopened container. Opened containers can be stored by keeping the container well closed. The containers need to be stored frost free. Avoid direct sunlight or strong heat.

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de

Form of supply

5 liter bucket:	60 buckets per pallet
10 liter bucket:	44 buckets per pallet
25 liter bucket:	18 buckets per pallet
5 liter can:	60 cans per pallet
10 liter can:	60 cans per pallet
20 liter can:	24 cans per pallet

Cleaning agent

At skin contact: Hand washing paste

Tools and other objects can be cleaned with water when fresh and when set with DOBAU®- SWS Bit-Cleanser.

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/23

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de