

DOBAU[®]-Voranstrich L



DOBAU[®]- PRIMER L

Low-viscosity, solvent-based bituminous primer

Use

DOBAU[®]- Voranstrich L is a primer and adhesive base with high penetration capacity into mineral substrates such as concrete, brickwork and rendering. DOBAU[®]- Voranstrich L serves as a primer for hot or cold applied bituminous paint and coating compounds, plus bituminous roofing membranes.

Properties

DOBAU[®]- Voranstrich L is characterised by the following features:

- fulfils the requirements of DIN 18 195 and AIB DS 835
- supplied ready for application
- good adhesion on bituminous and mineral substrates
- resistant to aqueous solutions, diluted acids, salts, lime, cement, etc.
- fast setting
- binds dust

Application instructions

Weather conditions

When using DOBAU[®]- Voranstrich L, the component surface temperature and ambient temperature must not fall below 5 °C. The effects of water, rain and frost must be avoided during the processing and drying phase.

Substrate and implementation

The substrate to be coated must be dry and free of oils, grease and loose components. Before processing, DOBAU[®]- Voranstrich L must be fully homogenized by stirring. DOBAU[®]- Voranstrich L can be applied by brushing or spraying.

Theoretical material consumption

approx. 0.2 - 0.3 kg/m², depending on substrate

Storage

DOBAU[®]- Voranstrich L can be stored for at least 12 months in an unopened container. The packaging must be stored frost-free. Avoid direct sunlight or strong heat. The „Ordinance on Flammable Liquids (VbF)“ applies.

Form of supply

5 l- and 10 l- packaging

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de

Cleaning agent

When set: DOBAU®- SWS Bit-Cleanser, common solvents or benzine
In case of skin contact: Hand cleansing paste

Technical data

Type of binder: Bitumen
Type of solvent: White spirit
Nature: Low-viscosity
Flashpoint (DIN 53 213): approx. 30 °C
Density (DIN 52 004): approx. 0.84 g/cm³

Hazard warnings: **R10 Flammable**

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/23

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de