

PROXAN[®]-CP-G



- alkyl silane based
- for non-absorbent substrates

Primer PROXAN[®]- CP-G is a water-clear, low-viscosity primer for polysulphide sealants on non-absorbent substrates. It is a component of the test certificates and building approvals of the PROXAN[®]- products.

Use

Primer for non-absorbent substrates such as split clinkers, glazed ceramic, plastics (PVC, polyester, melamine resin, metals (aluminium, steel, copper, zinc) and glass. We recommend requesting additional information from the manufacturer.

Application

The substrate must be dry, free of dust and grease and without any loose components. Old coatings must be removed. The primer must be uniformly applied using a brush. After a flash-off time of 10 to 30 minutes the sealant can be introduced.

Supply form

Metal bottle 400 ml, 18 bottles per carton

Technical data

	PROXAN [®] - CP-G
Chemical basis:	Alkylsilan
Processing time:	10 to 30 minutes
Colour:	water clear
Density:	approx. 0,8 g/ml
Consumption:	0,005-0,01 l/linear m (depending on joint dimensions)

Storage

Can be stored for 12 months if dry and at temperatures below +25 °C in closed original container.

Data on:

Ordinance for the Storage of Flammable Liquids (VbF),

Technical Rules of Hazardous Substances (TRGs),

Water Hazard Class (WGK)

please see our safety data sheet.

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de

Producer

Plant Greiz

Disposal

Primer PROXAN®- CP-G is waste requiring special monitoring and must be disposed of as such. More information can be found in the safety data sheet.

Work safety

The essential physical, safety-relevant, toxicological and ecological data can be found in the EC safety data sheet for work with chemical substances. Observe the regulations of the Hazardous Substances Ordinance.

Important



The above mentioned information is in accordance with our current state of knowledge and our previous experiences. They make no claim to be complete. The changing conditions at the application, the different working conditions at the construction site as well as a variety of materials exclude any claim to liability from this information. The best assurance against possible failures will be achieved through your own tests for the intended application purpose. Our application engineering will be pleased to advise you.

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/20

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

 Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany +49 231 395797 - 37  info@dga.de**Producer**

Plant Greiz