

# PROXAN<sup>®</sup>-CP-S



- EP-resin based
- sprayable, for absorbent substrates

Primer PROXAN<sup>®</sup>- CP-S is a sprayable, two-component primer for polysulphide sealants that are primarily used on floors. It is a component of the test certificates and building approvals of the PROXAN<sup>®</sup>- products.

## Use

Primer PROXAN<sup>®</sup>- CP-S is suitable for the pre-treatment of porous, absorbent surfaces such as concrete, masonry, wood (without varnish or top coat) – especially on floors. Due to its low viscosity, PROXAN<sup>®</sup>- CP-S Primer is particularly suitable for application by spraying.

## Application

The substrate must be dry, free of dust and grease and without any loose components. Components A and B are thoroughly mixed and the primer evenly applied to the joint flanks by spraying or using a brush. After a flash-off time of 30 minutes to 2 hours (depending on temperature) the sealant can be introduced. The primer must not have fully dried. If more than 24 hours have passed, the old layer must be roughened and new primer applied.

## Supply form

Combination container of 1 litre (component A + B), 10 packs per carton  
Combination container of 5 litre (component A + B)

## Technical data

	PROXAN <sup>®</sup> - CP-S
Chemical basis:	Epoxy resin
Processing time:	min. 6 hours
Flash-off time:	30 minutes to 2 hours (depending on temperature)
Mixing ratio:	A : B = 1 : 1 Mass portions
Consumption:	Depending on the application method and joint dimensions

## Storage

Can be stored for 12 months if dry and at temperatures below +25 °C in closed original container.

Data on:

Ordinance for the Storage of Flammable Liquids (VbF),  
Technical Rules of Hazardous Substances (TRGs),  
Water Hazard Class (WGK)  
please see our safety data sheet.

## Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37    @ info@dga.de    🌐 www.dga.de

**Producer**

Plant Greiz

**Disposal**

Fully cured PROXAN®- CP-S Primer can be disposed of as municipal waste. The individual A and B components are wastes requiring special monitoring and must be disposed of as such. More information can be found in the safety data sheet.

**Work safety**

The essential physical, safety-relevant, toxicological and ecological data can be found in the EC safety data sheet for work with chemical substances. Observe the regulations of the Hazardous Substances Ordinance.

**Important**

The above mentioned information is in accordance with our current state of knowledge and our previous experiences. They make no claim to be complete. The changing conditions at the application, the different working conditions at the construction site as well as a variety of materials exclude any claim to liability from this information. The best assurance against possible failures will be achieved through your own tests for the intended application purpose. Our application engineering will be pleased to advise you.

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at [www.dga.de](http://www.dga.de).

Rev.: 02/20

**Central Sales**

Dortmunder Gußasphalt GmbH &amp; Co. KG

 Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany +49 231 395797 - 37  [info@dga.de](mailto:info@dga.de)  [www.dga.de](http://www.dga.de)**Producer**

Plant Greiz