

PROXAN[®]-CP-SR



- EP-resin based
- for applications on floors

Primer PROXAN[®]- CP-SR is a two-component primer formulated specially for the PROXAN[®]- KV 2 G-S joint sealant, which is preferentially used in ground applications.

Use

Primer PROXAN[®]- CP-SR is suitable for the pre-treatment of porous, absorbent surfaces such as concrete, masonry, wood (without varnish or top coat) – especially on floors.

Application

The substrate must be dry, free of dust and grease and without any loose components. Mix components A and B thoroughly and apply the primer evenly with a brush. After a flash-off time of 30 minutes to 2 hours (depending on temperature) the sealant can be introduced. The primer must not have fully dried. If more than 24 hours have passed, the old layer must be roughened and new primer applied. Make sure that a film of moisture has not formed on the primer surface on account of it falling below the dew point temperature.

Supply form

Combined container each 1 litre (component A + B), 10 containers per carton.

Technical data

	PROXAN [®] - CP-SR
Chemical basis:	Epoxy resin
Processing time:	approx. 2 to 3 hours
Flash-off time:	30 minutes to 2 hours (depending on temperature)
Mixing ratio:	A : B = 100 : 45 mass portions
Consumption:	0,01 bis 0,02 l/linear m (depending on joint dimensions)

Storage

Can be stored for 12 months if dry and at temperatures below +25 °C in closed original container.

Data on:

Ordinance for the Storage of Flammable Liquids (VbF),
Technical Rules of Hazardous Substances (TRGs),

Water Hazard Class (WGK)

please see our safety data sheet.

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de

Producer

Plant Greiz

Disposal

Fully cured PROXAN®- CP-SR Primer can be disposed of as municipal waste. The individual A and B components are wastes requiring special monitoring and must be disposed of as such. More information can be found in the safety data sheet.

Work safety

The essential physical, safety-relevant, toxicological and ecological data can be found in the EC safety data sheet for work with chemical substances. Observe the regulations of the Hazardous Substances Ordinance.

Important

The above mentioned information is in accordance with our current state of knowledge and our previous experiences. They make no claim to be complete. The changing conditions at the application, the different working conditions at the construction site as well as a variety of materials exclude any claim to liability from this information. The best assurance against possible failures will be achieved through your own tests for the intended application purpose. Our application engineering will be pleased to advise you.

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/20

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de

Producer

Plant Greiz