

PROXAN®-FLEXOMAT



Application device for two-component, cold-workable joint sealing compounds



Description

The PROXAN®- FLEXOMAT 8 bar application device is especially designed for applying ready-mixed 25 l containers of pourable polysulphide sealant. With the PROXAN®- FLEXOMAT 8 bar you can process up to 100 l per hour. The pressure vessel is designed for up to 8 bar and can accommodate containers with up to 25 l contents.

Use

Two workers are required to operate the PROXAN®- FLEXOMAT 8 bar. One person operates the PROXAN®- FLEXOMAT and one person guides a provided hand lance. Work can be carried out comfortably while standing. The hose comprises consumable material and is replaced after each use. Cleaning other parts can be done with PROXAN®- PR-S and PROXAN®- PR 4.

Technical data

Empty weight:	approx. 110 kg
Length:	approx. 1100 mm
Height:	approx. 1300 mm
Width:	approx. 580 mm
Motor:	HONDA GX 100 with 2,1 kw
Max pressure:	8 bar
For containers up to::	25 l

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/22

Technical data sheet page 1

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de 🌐 www.dga.de