

PROXAN[®]-PR 4



Special cleaner for removing unhardened polysulphide joint sealants from application tools and for degreasing substrates.

Application

PROXAN[®]- PR 4 is used to clean metallic tools to which unhardened PROXAN[®]- joint sealant residues have adhered. Depending on the degree of soiling, the tools are either placed in the cleaner and then cleaned with a rag, or the cleaner is placed directly on a rag and the soiling is removed by rubbing. When used on plastic or coated components, check whether the plastic or the surface is damaged. Hardened sealant residues swell when cleaner is applied. The residues can then be removed mechanically. Rubber components, such as seals, may not be stored in PROXAN[®]- PR 4, as they become unusable due to swelling.

The cleaner is also suitable for cleaning and degreasing joints.

Supply form

1.0 litre metal flask 10 flasks/box
10 litre PE canister

Storage

Dry and at temperatures below +25 °C; do not store near radiators.
Avoid direct sunlight on the packaging.

Occupational safety

The essential physical, safety-relevant, toxicological and ecological data can be found in the safety data sheet for handling chemical substances. Observe the regulations of the Hazardous Substances Ordinance.

Disposal

Do not allow to enter the sewage system or water bodies. PROXAN[®]- PR 4 must be disposed of as special waste compliant with waste code number 160305. The responsible local authorities such as the district administration, environmental protection agency or factories inspectorate are responsible for providing information for correct disposal.

Attention

The above information corresponds to the current state of knowledge and our previous experience. It does not claim to be exhaustive. The changing circumstances during use, the different working conditions on the construction site and the large number of possible materials preclude any liability for this information. The best security against possible failures is achieved by performing your own tests for the intended application. Our application technology staff will be happy to advise you.

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at www.dga.de.

Rev.: 01/20

Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37 @ info@dga.de

Producer

Plant Greiz