

# PROXAN®-PR-S



Sprayable special cleaner for removing unhardened polysulphide joint sealants from application tools and for degreasing substrates.

## Application

PROXAN®- PR-S is used to clean metallic tools to which unhardened PROXAN®- joint sealant residues have adhered. The tools are sprayed with cleaner and the residues removed using a rag. When used on plastic or coated components, check whether the plastic or the surface is damaged. Hardened sealant residues swell when cleaner is applied. The residues can then be removed mechanically. Rubber components, such as seals, may not be stored in PROXAN®- PR-S, as they become unusable due to swelling. The cleaner is also suitable for cleaning and degreasing joints.

## Supply form

400 ml spray can                      12 cans/box

## Storage

Keep the containers properly closed and store in a cool, well ventilated location. Keep away from heat, hot surfaces, sparks, open flames and other sources of ignition. Protect from sunlight. Containers should only be accessible to authorised persons.

## Occupational safety

PROXAN®- PR-S is inflammable and is a skin degreaser. Wear safety glasses and suitable protective gloves when working with the cleaner. Ensure sufficient ventilation. Do not carry out cleaning work near heat sources. No smoking. Please see our safety data sheet for further information.

## Disposal

Do not allow to enter the sewage system or water bodies. PROXAN®- PR-S and its containers must be disposed of as hazardous waste compliant with waste code 16 05 04 (gases in pressurised containers and used chemicals; gases contained in hazardous substances in pressurised containers...).

## Attention

The above information corresponds to the current state of knowledge and our previous experience. It does not claim to be exhaustive. The changing circumstances during use, the different working conditions on the construction site and the large number of possible materials preclude any liability for this information. The best security against possible failures is achieved by performing your own tests for the intended application. Our application technology staff will be happy to advise you.

This product information corresponds to our latest available information. The processor is obliged to test the suitability and application options for the intended purpose. We shall be pleased to advise if you have any questions about our product. Our Terms and Conditions of Business apply, which can be found at [www.dga.de](http://www.dga.de).

Rev.: 01/20

## Central Sales

Dortmunder Gußasphalt GmbH & Co. KG

✉ Am Hafenbahnhof 10 ■ 44147 Dortmund ■ Germany

☎ +49 231 395797 - 37    @ info@dga.de

**Producer**

Plant Greiz